KOMBIC 150 DOWNLIGHT


K21RD2023RF940NWW



KOMBIC 150 RD 2400 IP23 9NW RF FL WH/WH

Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 66.000 L90 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Flood to achieve a controlled light distribution and low UGR<19.



Finish: Matte white RAL 9010

Weight: 704 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.172 lm °K: 4000 Plum: 19,1W CRI: 90 Efficacy: 113,7 lm/w R9: 68 UGR: <19 MacAdam: 3

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 66.000 L90 B10 (Ta=25°C) Gear: Electronic

17W Power:

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













KOMBIC 150 DOWNLIGHT



K21RD2023RF940NWW

KOMBIC 150 RD 2400 IP23 9NW RF FL WH/WH

PHOTOMETRIC DATA:

$$\label{eq:control_eq} \begin{split} \text{K21RD2023RF940NWW} \\ \eta &= 100\% \\ \text{Imax} &= 2155 \text{ cd/klm} \\ \text{UTE:} \end{split}$$

CIE: 99 100 100 100 100

