KOMBIC 150 DOWNLIGHT

LAMP Worktitude for light

K21RD2023RW927DBB



KOMBIC 150 RD 2400 IP23 9VWW RF WF D B/B


Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in black finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 66.000 L90 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Wide Flood to achieve a controlled light distribution and low UGR<19.

Finish: Matte black RAL 9011

Weight: 704 g

Installation: Recessed



TECHNICAL SPECIFICATIONS:

Light output: 2.002 lm °K: 2700 Plum: 19,1W CRI: 90 Efficacy: 104,8 lm/w R9: 53 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 66.000 L90 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 17W

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













KOMBIC 150 DOWNLIGHT



K21RD2023RW927DBB

KOMBIC 150 RD 2400 IP23 9VWW RF WF D B/B

PHOTOMETRIC DATA:

K21RD2023RW927DBB η = 100% lmax = 1345 cd/klmUTE:

CIE: 99 100 100 100 100

