

KOMBIC 150 DOWNLIGHT

K21RD20400P830DRW



KOMBIC 150 RD 2100 IP43 WW OPAL DA BR/WH


Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Shiny metalized interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L90 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: BRILLIANT METALLIC POLYCARBONATE

Weight: 704 g


Installation: Recessed



TECHNICAL SPECIFICATIONS:

Light output:	1.488 lm	°K :	3000
Plum:	13,7W	CRI :	80
Efficacy:	111,1 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L90 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	12W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 150 DOWNLIGHT

K21RD20400P830DRW

KOMBIC 150 RD 2100 IP43 WW OPAL DA BR/WH

PHOTOMETRIC DATA :

