Product datasheet

KOMBIC 150 DOWNLIGHT

K21RD2040OP840DMW

KOMBIC 150 RD 2100 IP43 NW OPAL DA MA/WH

Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L90 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: metalized polycarbonate mate

Weight: 704 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.486 lm	**ºK :**	4000
Plum:	13,7W	**CRI :**	80
Efficacy:	108,5 lm/w	**MacAdam:**	3
Type:	COB	**Power Supply:**	220-240V 50/60Hz
LED Lifetime:	50.000 L90 B10 (Ta=25ºC)	**Gear:**	Adjustable DALI
Power:	12W		

Light output tolerance +/- 10%

AI · ø 145 · IP 20 INT 43 EXT · LED 4000 K · 2-40 mm · PC · 650º · CE · EPD · 5 · Group 0 En 62471

CUSTOM MADE OPTIONS:

1-10V · lm · LED RETAIL · PUSH · TRIAC · K

KOMBIC 150 DOWNLIGHT

K21RD2040OP840DMW **KOMBIC 150 RD 2100 IP43 NW OPAL DA MA/WH**

PHOTOMETRIC DATA :

K21RD2040OP840NMW

η = 100%

Imax = 988 cd/klm

UTE: 1,00A

CIE: 87 100 100 100 100









LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Data according to regulations 2019/2020/EU and 2019/2015/EU