KOMBIC 150 DOWNLIGHT

K21RD2040OP930NWW

KOMBIC 150 RD 2400 IP43 9WW OP WH/WH

Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L90 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010

Weight: 704 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 1.720 lm °K: 3000 Plum: 19,8W CRI: 90 Efficacy: 86,9 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

18W Power:

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:

















KOMBIC 150 DOWNLIGHT



K21RD2040OP930NWW

KOMBIC 150 RD 2400 IP43 9WW OP WH/WH

PHOTOMETRIC DATA:

K21RD2040OP930NWW η = 100% Imax = 833 cd/klm UTE: 1,00B

CIE: 79 96 99 100 100















