


KOMBIC 150 DOWNLIGHT

K21RD20400P940NMW



KOMBIC 150 RD 2400 IP43 9NW OP MA/WH

Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate


Weight: 704 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.797 lm	°K :	4000
Plum:	19,8W	CRI :	90
Efficacy:	90,8 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L70 B10 (Ta=25°C)	Gear:	Electronic
Power:	18W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 150 DOWNLIGHT

K21RD20400P940NMW

KOMBIC 150 RD 2400 IP43 9NW OP MA/WH

PHOTOMETRIC DATA :

