Product datasheet

KOMBIC 150 DOWNLIGHT

K21RD2040OP940NMW

KOMBIC 150 RD 2400 IP43 9NW OP MA/WH

Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: metalized polycarbonate mate

Weight: 704 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.797 lm	**ºK :**	4000
Plum:	19,8W	**CRI :**	90
Efficacy:	90,8 lm/w	**MacAdam:**	3
Type:	COB	**Power Supply:**	220-240V 50/60Hz
LED Lifetime:	50.000 L70 B10 (Ta=25ºC)	**Gear:**	Electronic
Power:	18W		

Light output tolerance +/- 10%

CUSTOM MADE OPTIONS:

KOMBIC 150 DOWNLIGHT

K21RD2040OP940NMW **KOMBIC 150 RD 2400 IP43 9NW OP MA/WH**

PHOTOMETRIC DATA :

K21RD2040OP940NMW

η = 100%

Imax = 988 cd/klm

UTE: 1,00A

CIE: 87 100 100 100 100











Melanopic Lux Ratio: 0.756







LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Data according to regulations 2019/2020/EU and 2019/2015/EU