

KOMBIC 150 DOWNLIGHT

K21RD2055OP830DMW




KOMBIC 150 RD 2100 IP55 WW OPAL DA MA/WH

Description:


Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L90 B10. With IP55 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate

Weight: 704 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.427 lm	%K :	3000
Plum:	13,7W	CRI :	80
Efficacy:	104,2 lm/w	MacAdam:	3
Type:	COB PHILIPS	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L90 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	12W		

Light output tolerance +/- 10%


CUSTOM MADE OPTIONS:



KOMBIC 150 DOWNLIGHT

K21RD2055OP830DMW

KOMBIC 150 RD 2100 IP55 WW OPAL DA MA/WH

PHOTOMETRIC DATA :

