


KOMBIC 150 DOWNLIGHT

K21RD2065OP830NWW




KOMBIC 150 RD 2100 IP65 WW OPAL WH/WH

Description:

Round recessed downlight model KOMBIC 150 RD 2100 IP65 WW OPAL WH/WH, LAMP brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Reflector made of polycarbonate. Matte metallic interior reflector and frame in white finish, and optical film, die cast aluminium heat sink. Model for LED COB, with 3000K colour temperature, CRI80 and control gear included. IP65 protection rating. Insulation class II. Group 0 photobiological safety. Lifetime: 50.000h L90 B10.

Finish: Matte white RAL 9010**Weight:** 704 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	1.473 lm	°K :	3000
Plum:	13,4W	CRI :	80
Efficacy:	109,9 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L90 B10 (Ta=25°C)	Gear:	Electronic
Power:	12W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 150 DOWNLIGHT

K21RD2065OP830NWW

KOMBIC 150 RD 2100 IP65 WW OPAL WH/WH

PHOTOMETRIC DATA :

