

## KOMBIC 150 DOWNLIGHT

K21RD3023RF830NMW



## KOMBIC 150 RD 2800 IP23 WW RF FL MA/WH

## Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 66.000 L90 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Flood to achieve a controlled light distribution and low UGR<19.


**Finish:** metalized polycarbonate mate

**Weight:** 704 g

**Installation:** Recessed

## TECHNICAL SPECIFICATIONS:

<b>Light output:</b>	2.390 lm	<b>°K :</b>	3000
<b>Plum:</b>	19,1W	<b>CRI :</b>	80
<b>Efficacy:</b>	125,1 lm/w	<b>MacAdam:</b>	3
<b>UGR:</b>	<19	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Type:</b>	COB	<b>Gear:</b>	Electronic
<b>LED Lifetime:</b>	66.000 L90 B10 (Ta=25°C)		
<b>Power:</b>	17W		

*Light output tolerance +/- 10%*


## CUSTOM MADE OPTIONS:



KOMBIC 150 DOWNLIGHT

K21RD3023RF830NMW

KOMBIC 150 RD 2800 IP23 WW RF FL MA/WH

PHOTOMETRIC DATA :

