KOMBIC 150 DOWNLIGHT


K21RD3023RF927NBW



KOMBIC 150 RD 3200 IP23 9VWW RF FL BK/WH

Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 66.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Flood to achieve a controlled light distribution and low UGR<19.



Finish: Matte black RAL 9011

Weight: 704 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.622 lm °K: 2700 Plum: 28,3W CRI: 90 Efficacy: 92,7 lm/w R9: 53 UGR: <19 MacAdam: 3

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 66.000 L80 B10 (Ta=25°C) Gear: Electronic

25W Power:

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:





















KOMBIC 150 DOWNLIGHT



K21RD3023RF927NBW

KOMBIC 150 RD 3200 IP23 9VWW RF FL BK/WH

PHOTOMETRIC DATA:

K21RD3023RF927NBW η = 100% Imax = 2122 cd/klm UTE:

CIE: 100 100 100 100 100

