KOMBIC 150 DOWNLIGHT

Worktitude for light


K21RD3023RW930DWW



KOMBIC 150 RD 3200 IP23 9WW RF WF DA W/W

Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 66.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Wide Flood to achieve a controlled light distribution and low UGR<19.



Finish: Matte white RAL 9010

Weight: 704 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.780 lm °K: 3000 Plum: 28,3W CRI: 90 Efficacy: 98,2 lm/w R9: 54 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 66.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 25W

Light output tolerance +/- 10%























Group 0 En 62471

CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













KOMBIC 150 DOWNLIGHT



K21RD3023RW930DWW

KOMBIC 150 RD 3200 IP23 9WW RF WF DA W/W

PHOTOMETRIC DATA:

K21RD3023RW930DWW η = 100% lmax = 1342 cd/klmUTE:

CIE: 98 100 100 100 100



