## **KOMBIC 150 DOWNLIGHT**

## K21RD3023RW940DWW



## **KOMBIC 150 RD 3200 IP23 9NW RF WF DA W/W**

## Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 66.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Wide Flood to achieve a controlled light distribution and low UGR<19.



Finish: Matte white RAL 9010

Weight: 704 g

Installation: Recessed

## **TECHNICAL SPECIFICATIONS:**

Light output: 2.962 lm °K: 4000 Plum: 28,3W CRI: 90 Efficacy: 104,7 lm/w R9: 68 UGR: <19 MacAdam: 3

Type: СОВ Power Supply: 220-240V 50/60Hz LED Lifetime: 66.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

25W Power:

# Light output tolerance +/- 10%





























# **CUSTOM MADE OPTIONS:**





















# **KOMBIC 150 DOWNLIGHT**



K21RD3023RW940DWW

# **KOMBIC 150 RD 3200 IP23 9NW RF WF DA W/W**

# **PHOTOMETRIC DATA:**

K21RD3023RW940DWW  $\eta$  = 100% lmax = 1342 cd/klmUTE:

CIE: 98 100 100 100 100















