## **KOMBIC 150 DOWNLIGHT**



## K21RD3040OP930NWW



## KOMBIC 150 RD 3200 IP43 9WW OP WH/WH


## Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L90 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010

Weight: 704 g

Installation: Recessed



## **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.288 lm
 °K:
 3000

 Plum:
 27,7W
 CRI:
 90

 Efficacy:
 82,6 lm/w
 MacAdam:
 3

**Type:** COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 25W

## Light output tolerance +/- 10%





























## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU











## **KOMBIC 150 DOWNLIGHT**



K21RD3040OP930NWW

# KOMBIC 150 RD 3200 IP43 9WW OP WH/WH

## **PHOTOMETRIC DATA:**

K21RD3040OP930NWW  $\eta$  = 100% Imax = 833 cd/klm UTE: 1,00B

CIE: 79 96 99 100 100

