

KOMBIC 150 DOWNLIGHT

K21RD3040WF940NMW




KOMBIC 150 RD 3200 IP43 9NW WFL MA/WH

Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CR90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low UGR<19. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate

Weight: 704 g




Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.967 lm	°K :	4000
Plum:	28W	CRI :	90
Efficacy:	70,3 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	COB	Gear:	Electronic
LED Lifetime:	50.000 L70 B10 (Ta=25°C)		
Power:	25W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 150 DOWNLIGHT

K21RD3040WF940NMW

KOMBIC 150 RD 3200 IP43 9NW WFL MA/WH

PHOTOMETRIC DATA :

K21RD3040WF940NMW
 $\eta = 100\%$
 $I_{max} = 1186 \text{ cd/klm}$
 UTE:
 CIE: 98 100 100 100 100

