

KOMBIC 150 DOWNLIGHT




K21RD30VWMSWWW

KOMBIC 150 RD 2800 MS VWF WI WH/WH.

Description:

Downlight recessed round model KOMBIC 150 RD 2800 MS WI Lamp brand. Extruded aluminium heatsink with active dissipation. Model for Multispectral LED equipped with 7 channels to provide any type of visible light spectrum between 420 nm and 730 nm wavelengths. Wireless or wired connectivity available. IP20 or IP65 protecting rating. Insulation class II. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010

Weight: 704 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	2.382 lm	CRI :	90
Plum:	67W	MacAdam:	2
Efficacy:	35,6 lm/w	Power Supply:	220-240V 50/60Hz
UGR:	30	Gear:	Electronic
Type:	HI POWER LEDMOTIVE		
LED Lifetime:	50.000 (Ta=25°C)		
Power:	60W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 150 DOWNLIGHT

K21RD30VWMSWWW

KOMBIC 150 RD 2800 MS VWF WI WH/WH.

PHOTOMETRIC DATA :

