

KOMBIC 150 DOWNLIGHT


K21RD30WFMSWRW



KOMBIC 150 RD 2800 MS WFL WI BR/WH.

Description:

Downlight recessed round model KOMBIC 150 RD 2800 MS WI Lamp brand. Extruded aluminium heatsink with active dissipation. Model for Multispectral LED equipped with 7 channels to provide any type of visible light spectrum between 420 nm and 730 nm wavelengths. Wireless or wired connectivity available. IP20 or IP65 protecting rating. Insulation class II. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: BRILLIANT METALLIC POLYCARBONATE**Weight:** 704 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	2.500 lm	CRI :	90
Plum:	67W	MacAdam:	2
Efficacy:	37,3 lm/w	Power Supply:	220-240V 50/60Hz
UGR:	26	Gear:	Electronic
Type:	HI POWER LEDMOTIVE		
LED Lifetime:	50.000 (Ta=25°C)		
Power:	60W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 150 DOWNLIGHT

K21RD30WFMSWRW

KOMBIC 150 RD 2800 MS WFL WI BR/WH.

PHOTOMETRIC DATA :

