

KOMBIC 150 DOWNLIGHT



K21RD3540EL840NBB




KOMBIC 150 RD 3700 IP43 NW EL BK/BK

Description:

LAMP Round recessed downlight KOMBIC 150 RD 3700 . Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Elliptical optic option is the perfect choice for lighting walkways and longitudinal areas such as counters or areas adjacent to work areas. This product allows for increased spacing between luminaires, reducing the effect of residual light on walls and providing a pleasant atmosphere in the space.Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 4000K and CRI80. Electronic ON OFF gear included. IP44 rated. Insulation Class II. Photobiological safety group 0. LED life time: 60.000 L80 B10. Available finishes: White and black. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte black RAL 9011

Weight: 725 g




Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	2.965 lm	°K :	4000
Plum:	27,7W	CRI :	80
Efficacy:	107 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	60.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	25W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 150 DOWNLIGHT

K21RD3540EL840NBB

KOMBIC 150 RD 3700 IP43 NW EL BK/BK

PHOTOMETRIC DATA :

