Product datasheet

KOMBIC 150 DOWNLIGHT

K21RD3540OP840DWW

KOMBIC 150 RD 3700 IP43 NW OPAL DA WH/WH

Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010

Weight: 704 g



Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	2.874 lm	**ºK :**	4000
Plum:	28W	**CRI :**	80
Efficacy:	83,4 lm/w	**MacAdam:**	3
Type:	COB	**Power Supply:**	220-240V 50/60Hz
LED Lifetime:	50.000 L70 B10 (Ta=25ºC)	**Gear:**	Adjustable DALI
Power:	25W		

Light output tolerance +/- 10%

IP 20 INT 43 EXT

EPD

Group 0 En 62471

CUSTOM MADE OPTIONS:

1-10V · lm · LED RETAIL · PUSH · TRIAC · K