

## KOMBIC 150 DOWNLIGHT

K21RD35400P840NRW



## KOMBIC 150 RD 3700 IP43 NW OPAL BR/WH

## Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Shiny metalized interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: BRILLIANT METALLIC POLYCARBONATE


Weight: 704 g

Installation: Recessed

## TECHNICAL SPECIFICATIONS:

Light output:	2.904 lm	°K :	4000
Plum:	28W	CRI :	80
Efficacy:	104,8 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L70 B10 (Ta=25°C)	Gear:	Electronic
Power:	25W		

Light output tolerance +/- 10%



## CUSTOM MADE OPTIONS:



KOMBIC 150 DOWNLIGHT

K21RD3540OP840NRW

KOMBIC 150 RD 3700 IP43 NW OPAL BR/WH

PHOTOMETRIC DATA :

