

## KOMBIC 150 DOWNLIGHT

K21RD3540WW830NBB




## KOMBIC 150 RD 3700 IP43 WW WW BK/BK

**Description:**

LAMP Round recessed downlight KOMBIC 150 RD 3700. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Wallwasher optic option, suitable for vertical plane lighting or work areas surroundings. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP44 rated. Insulation Class II. Photobiological safety group 0. LED life time: 60.000 L80 B10. Available finishes: White and black. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** Matte black RAL 9011**Weight:** 725 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.945 lm	<b>°K :</b>	3000
<b>Plum:</b>	27,7W	<b>CRI :</b>	80
<b>Efficacy:</b>	70,2 lm/w	<b>MacAdam:</b>	3
<b>Type:</b>	COB	<b>Power Supply:</b>	220-240V 50/60Hz
<b>LED Lifetime:</b>	60.000 L80 B10 (Ta=25°C)	<b>Gear:</b>	Electronic
<b>Power:</b>	25W		

**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**

KOMBIC 150 DOWNLIGHT

K21RD3540WW830NBB

KOMBIC 150 RD 3700 IP43 WW WW BK/BK

PHOTOMETRIC DATA :

