

KOMBIC 150 SURFACE

K21SF2040OP930DWW




KOMBIC 150 SF 2400 IP43 9WW OP DA WH/WH

Description:

Suspended or ceiling mounting downlight model KOMBIC 150 SF by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010

Weight: 1.478 g



Installation: Surface

TECHNICAL SPECIFICATIONS:

| | | | |
|----------------------|--------------------------|----------------------|------------------|
| Light output: | 1.770 lm | °K : | 3000 |
| Plum: | 19,8W | CRI : | 90 |
| Efficacy: | 89,5 lm/w | MacAdam: | 3 |
| Type: | COB | Power Supply: | 220-240V 50/60Hz |
| LED Lifetime: | 50.000 L80 B10 (Ta=25°C) | Gear: | Adjustable DALI |
| Power: | 17,6W | | |

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 150 SURFACE

K21SF2040OP930DWW

KOMBIC 150 SF 2400 IP43 9WW OP DA WH/WH

PHOTOMETRIC DATA :

K21SF2040OP930DWW
 $\eta = 100\%$
 $I_{max} = 833 \text{ cd/klm}$
 UTE: 1,00B
 CIE: 79 96 99 100 100

