KOMBIC 150 SURFACE

Worktitude for light

K21SF2040OP930DWW



KOMBIC 150 SF 2400 IP43 9WW OP DA WH/WH


Description:

Suspended or ceiling mounting downlight model KOMBIC 150 SF by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of diecast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010

Weight: 1.478 g

Installation: Surface



TECHNICAL SPECIFICATIONS:

 Light output:
 1.770 lm
 °K:
 3000

 Plum:
 19,8W
 CRI:
 90

 Efficacy:
 89,5 lm/w
 MacAdam:
 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 17,6W

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













KOMBIC 150 SURFACE




K21SF2040OP930DWW


KOMBIC 150 SF 2400 IP43 9WW OP DA WH/WH


PHOTOMETRIC DATA:


K21SF2040OP930DWW η = 100% Imax = 833 cd/klm UTE: 1,00B


CIE: 79 96 99 100 100




















KOMBIC 150 SURFACE



ACCESORIES:

Suspension



Product code: Description:

KOMBIC 150 SF ADAPT. LATERAL CABLE BK

K21SUADLATBK



Product code:

K21SUADLATWH

Description:

KOMBIC 150 SF ADAPT. LATERAL CABLE WH