KOMBIC 150 SURFACE

K21SF2040OPWB3DMW



KOMBIC 150 SF 1800 IP43 WBW OP DA MA/WH


Description:

LAMP Suspended or ceiling mounting downlight model KOMBIC 150 SF. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and optical film. Heatsink made of diecast aluminium. COB LED WELLBEING, colour temperature 3000K with CRI95. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 60.000 L80 B10.. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD® available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate

Weight: 1.478 g

Installation: Surface



TECHNICAL SPECIFICATIONS:

Light output: 1.308 lm °K: 3000 Plum: 19W CRI: 95 Efficacy: 68,8 lm/w R9: 99 Type: СОВ MacAdam: 3

LED Lifetime: 60.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz Gear: Power: 17,1W Adjustable DALI

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













KOMBIC 150 SURFACE




K21SF2040OPWB3DMW


KOMBIC 150 SF 1800 IP43 WBW OP DA MA/WH


PHOTOMETRIC DATA:


K21SF2040OPWB3DMW η = 100% Imax = 985 cd/klm UTE: 1,00A


CIE: 86 100 100 100 100




















KOMBIC 150 SURFACE



ACCESORIES:

Suspension



Product code: Description:

K21SUADLATBK KOMBIC 150 SF ADAPT. LATERAL CABLE BK



Product code:

K21SUADLATWH

Description:

KOMBIC 150 SF ADAPT. LATERAL CABLE WH