KOMBIC 150 SURFACE



K21SF2040WFWB3NBB

- KOMBIC 150 SF 1800 IP43 WBW WFL BK/BK

Description:

Suspended or ceiling mounting downlight model KOMBIC 150 SF by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI95. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 86.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR<16. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte black RAL 9011

TECHNICAL SPECIFICATIONS:

 Light output:
 1.516 lm
 °K:
 3000

 Plum:
 20W
 CRI:
 95

 Efficacy:
 75,8 lm/w
 R9:
 98

UGR: <16

LED Lifetime: 86.000h L80 B10 (Ta=25°C)

Power: 17,3W

Light output tolerance +/- 10%

IP 43

EPD

CUSTOM MADE OPTIONS:



















KOMBIC 150 SURFACE





K21SF2040WFWB3NBB


KOMBIC 150 SF 1800 IP43 WBW WFL BK/BK


PHOTOMETRIC DATA:


K21SF2040WFWB3NBB η = 100% Imax = 1388 cd/klm UTE: CIE: 98 100 100 100 100

















KOMBIC 150 SURFACE



ACCESORIES:

Suspension



Product code:

Description: K21SUADLATBK KOMBIC 150 SF ADAPT. LATERAL CABLE BK

Product code:

K21SUADLATWH

Description:

KOMBIC 150 SF ADAPT. LATERAL CABLE WH