### **KOMBIC 150 SURFACE**



### K21SF2040WFWB4NWB

### - KOMBIC 150 SF 1800 IP43 WBN WFL WH/BK

### Description:

Suspended or ceiling mounting downlight model KOMBIC 150 SF by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI95. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 86.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR<16. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010

### **TECHNICAL SPECIFICATIONS:**

 Light output:
 1.673 lm
 °K:
 4000

 Plum:
 20W
 CRI:
 95

 Efficacy:
 83,7 lm/w
 R9:
 88

**UGR:** <16

**LED Lifetime:** 86.000h L80 B10 (Ta=25°C)

Power: 17,3W

#### Light output tolerance +/- 10%

IP 43

EPD

# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU











## **KOMBIC 150 SURFACE**



K21SF2040WFWB4NWB

## KOMBIC 150 SF 1800 IP43 WBN WFL WH/BK

### **PHOTOMETRIC DATA:**


K21SF2040WFWB4NWB  $\eta$  = 100%


lmax = 1344 cd/klm


1111ax - 1344 CU/KIIII


UTE: 1,00A


CIE: 95 99 100 100 100




















## **KOMBIC 150 SURFACE**



ACCESORIES:

Suspension



Product code:

Description: K21SUADLATBK KOMBIC 150 SF ADAPT. LATERAL CABLE BK

Product code:

K21SUADLATWH

Description:

KOMBIC 150 SF ADAPT. LATERAL CABLE WH