KOMBIC 150 SURFACE

K21SF2540WFWB3NBW

KOMBIC 150 SF 2500 IP43 WBW WFL BK/WH

Description:

Suspended or ceiling mounting downlight model KOMBIC 150 SF by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI95. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 86.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR<16. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte black RAL 9011

TECHNICAL SPECIFICATIONS:

Light output:	1.975 lm	°K :	3000
Plum:	28W	CRI :	95
Efficacy:	70,6 lm/w	R9 :	98
UGR:	<16		
LED Lifetime:	86.000h L80 B10 (Ta=25⁰C)		
Power:	24,9W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:




KOMBIC 150 SURFACE


K21SF2540WFWB3NBW

KOMBIC 150 SF 2500 IP43 WBW WFL BK/WH



PHOTOMETRIC DATA :





Product datasheet

KOMBIC 150 SURFACE

ACCESORIES :

Suspension



Product code: K21SUADLATBK

Description: KOMBIC 150 SF ADAPT. LATERAL CABLE BK



Product code: K21SUADLATWH

Description: KOMBIC 150 SF ADAPT. LATERAL CABLE WH

Worktitude for light