

K21SF2540WFWB4DBB

- KOMBIC 150 SF 2500 IP43 WBN WFL DA BK/BK

**Description:**

Suspended or ceiling mounting downlight model KOMBIC 150 SF by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI95. Luminaire with electronic wiring DALI included. Insolation Class I. Lifetime: 86.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR<16. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** Matte black RAL 9011**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	2.082 lm	<b>°K :</b>	4000
<b>Plum:</b>	28W	<b>CRI :</b>	95
<b>Efficacy:</b>	74,4 lm/w	<b>R9 :</b>	88
<b>UGR:</b>	<16		
<b>LED Lifetime:</b>	86.000h L80 B10 (Ta=25°C)		
<b>Power:</b>	24,9W		



*Light output tolerance +/- 10%***CUSTOM MADE OPTIONS:**

KOMBIC 150 SURFACE

K21SF2540WFWB4DBB

KOMBIC 150 SF 2500 IP43 WBN WFL DA BK/BK

PHOTOMETRIC DATA :



KOMBIC 150 SURFACE

ACCESORIES :

Suspension



Product code:  
K21SUADLATBK

Description:  
KOMBIC 150 SF ADAPT. LATERAL CABLE BK



Product code:  
K21SUADLATWH

Description:  
KOMBIC 150 SF ADAPT. LATERAL CABLE WH