

KOMBIC 150 SURFACE


K21SF3040OP930DWW




KOMBIC 150 SF 3200 IP43 9WW OP DA WH/WH

Description:

Suspended or ceiling mounting downlight model KOMBIC 150 SF by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.


Finish: Matte white RAL 9010**Weight:** 1.478 g**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

Light output:	2.288 lm	°K :	3000
Plum:	28W	CRI :	90
Efficacy:	81,7 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60H
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	25W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

K21SF30400P930DWW KOMBIC 150 SF 3200 IP43 9WW OP DA WH/WH

PHOTOMETRIC DATA :



KOMBIC 150 SURFACE

ACCESORIES :

Suspension



Product code:
K21SUADLATBK

Description:
KOMBIC 150 SF ADAPT. LATERAL CABLE BK



Product code:
K21SUADLATWH

Description:
KOMBIC 150 SF ADAPT. LATERAL CABLE WH