


K31RD3040OP840NMW



KOMBIC 200 RD 3000 IP44 NW OPAL MA/WH

Description:

RoundRecessedDownlight model KOMBIC 200 RD, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and matt metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model for MID POWER LED, with 3000K colour temperature and CRI 80 and control gear included. IP44 protection rating. Insulation class II. Photogiological safety group 0. Photobiological safety group 0. Lifetime: 50.000h L80 B10



Finish: metalized polycarbonate mate

Weight: 976 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.084 lm °K: 4000 Plum: 18,1W CRI: 80 Efficacy: 115,1 lm/w 3 MacAdam:

UGR: <19

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

Power: 17W

Light output tolerance +/- 10%



Type:







MID POWER LED











Power Supply:

Gear:

220-240V 50/60Hz

Electronic








































K31RD3040OP840NMW

KOMBIC 200 RD 3000 IP44 NW OPAL MA/WH

PHOTOMETRIC DATA:







H (m)	D (m)	Emax	Emed
1	1,61	1334	676
2	3,22	334	169
3	4,84	148	75
4	6,45	83	42



ACCESORIES:

Optical



Product code: ADRD250W

Description:

KOMBIC ACC. Ø250 ADAPTER RING WH.



Product code: DITRRD240B

Description:

DOMO 220/KOMBIC ACC.TRANSP GLASS BK.



Product code:

Description:

DITRRD240G DOMO 220/KOMBIC ACC.TRANSP GLASS GR.

DITRRD240W DOMO 220/KOMBIC ACC.TRANSP GLASS WH.



Product code: RIRD240B

Description:

DOMO 220/KOMBIC ACC. DECO RING BK.



Product code:

Description:

RIRD240G DOMO 220/KOMBIC ACC. DECO RING GR. RIRD240W DOMO 220/KOMBIC ACC. DECO RING WH.





27-11-2024