

KOMBIC 200 DOWNLIGHT


K31RD4040OP830NMW




KOMBIC 200 RD 4000 IP44 WW OPAL MA/WH

Description:

Round recessed downlight model KOMBIC 200 RD, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and matt metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model for MID POWER LED, with 3000K colour temperature and CRI 80 and control gear included. IP44 protection rating. Insulation class II. Photobiological safety group 0. Lifetime: 50.000h L80 B10

Finish: metalized polycarbonate mate**Weight:** 976 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	2.688 lm	°K :	3000
Plum:	25,4W	CRI :	80
Efficacy:	105,8 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	MID POWER LED	Gear:	Electronic
LED Lifetime:	50.000 L80 B10 (Ta=25°C)		
Power:	24W		


Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 200 DOWNLIGHT

K31RD4040OP830NMW

KOMBIC 200 RD 4000 IP44 WW OPAL MA/WH

PHOTOMETRIC DATA :



KOMBIC 200 DOWNLIGHT

ACCESORIES :

Optical



Product code:
ADRD250W

Description:
KOMBIC ACC. Ø250 ADAPTER RING WH.




Product code:
DITRRD240B

Description:
DOMO 220/KOMBIC ACC.TRANSF GLASS BK.



Product code:
DITRRD240G
DITRRD240W

Description:
DOMO 220/KOMBIC ACC.TRANSF GLASS GR.
DOMO 220/KOMBIC ACC.TRANSF GLASS WH.



Product code:
RIRD240B

Description:
DOMO 220/KOMBIC ACC. DECO RING BK.



Product code:
RIRD240G
RIRD240W

Description:
DOMO 220/KOMBIC ACC. DECO RING GR.
DOMO 220/KOMBIC ACC. DECO RING WH.

KOMBIC 200 DOWNLIGHT

