Product datasheet

KOMBIC 200 DOWNLIGHT

K31RD4040OP830NRW

KOMBIC 200 RD 4000 IP44 WW OPAL BR/WH

Description:

Round recessed downlight model KOMBIC 200 RD, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and bright metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model for MID-POWER LED, with 3000K colour temperature and CRI 80 and control gear included. IP44 protection rating. Insulation class II. Photobiological safety group 0. Lifetime: 50.000h L80 B10




Finish: BRILLIANT METALLIC POLYCARBONATE
Weight: 976 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	2.800 lm	°K :	3000
Plum:	25,4W	CRI :	80
Efficacy:	110,2 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Туре:	MID POWER LED	Gear:	Electronic
LED Lifetime:	50.000 L80 B10 (Ta=25⁰C)		
Power:	24W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light

KOMBIC 200 DOWNLIGHT

K31RD4040OP830NRW

KOMBIC 200 RD 4000 IP44 WW OPAL BR/WH



PHOTOMETRIC DATA :

9241370	180°	alpha = 54,6°	H (m)	D (m)	Emax	Emed
η = 100% Imax = 947 cd/klm			1	1,03	2647	1631
UTE: 1,00B + 0,00T CIE: 78 98 100 100 100	90° 90°		2	2,07	662	408
			3	3,10	294	181
	0°		4	4,13	165	102

KOMBIC 200 DOWNLIGHT

ACCESORIES :

Optical



Product code: ADRD250W

Product code:

DITRRD240G

DITRRD240W

Description: KOMBIC ACC. Ø250 ADAPTER RING WH.



Product code: DITRRD240B

Description: DOMO 220/KOMBIC ACC.TRANSP GLASS BK.

Worktitude for light



Description: DOMO 220/KOMBIC ACC.TRANSP GLASS GR. DOMO 220/KOMBIC ACC.TRANSP GLASS WH.



Product code: RIRD240B





Product code:Description:RIRD240GDOMO 220/KOMBIC ACC. DECO RING GR.RIRD240WDOMO 220/KOMBIC ACC. DECO RING WH.