

KOMBIC 200 DOWNLIGHT


K31RD4040OP840DRW




KOMBIC 200 RD 4000 IP44 NW OPAL DA BR/WH

Description:

Round recessed downlight model KOMBIC 200 RD, LAMP brand. Interior diffuser made of opal polycarbonate specially for LED, injection aluminium dissipator and torikit type easy-fit fastening system. Model for MID-POWER LED, with 3000K colour temperature and CRI 80 and control DALI gear included. IP44 protection rating. Insulation class II. Lifetime: 50.000h L80 B10

Finish: BRILLIANT METALLIC POLYCARBONATE**Weight:** 976 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	2.944 lm	°K :	4000
Plum:	25,4W	CRI :	80
Efficacy:	115,9 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	MID POWER LED	Gear:	Adjustable DALI
LED Lifetime:	50.000 L80 B10 (Ta=25°C)		
Power:	24W		


Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 200 DOWNLIGHT

K31RD4040OP840DRW

KOMBIC 200 RD 4000 IP44 NW OPAL DA BR/WH

PHOTOMETRIC DATA :



ACCESORIES :

Optical




Product code:

ADRD250W

Description:

KOMBIC ACC. Ø250 ADAPTER RING WH.



Product code:

DITRRD240B

Description:

DOMO 220/KOMBIC ACC. TRANSP GLASS BK.



Product code:

DITRRD240G

Description:

DOMO 220/KOMBIC ACC. TRANSP GLASS GR.

DITRRD240W

DOMO 220/KOMBIC ACC. TRANSP GLASS WH.



Product code:

RIRD240B

Description:

DOMO 220/KOMBIC ACC. DECO RING BK.



Product code:

RIRD240G

Description:

DOMO 220/KOMBIC ACC. DECO RING GR.

RIRD240W

DOMO 220/KOMBIC ACC. DECO RING WH.