

K31RD5040OP840DMW



KOMBIC 200 RD 5000 IP44 NW OPAL DA MA/WH

Description:

Round recessed downlight model KOMBIC 200 RD, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and matt metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model for MID POWER LED, with 4000K colour temperature and CRI 80 and control DALI gear included. IP44 protection rating. Insulation class II. Lifetime: 50.000h L70 B10

Finish: metalized polycarbonate mate

Weight: 1.536 g



Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 3.845 lm
 °K:
 4000

 Plum:
 38,1W
 CRI:
 80

 Efficacy:
 100,9 lm/w
 MacAdam:
 3

 Type:
 MID POWER LED
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L70 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 36W

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU


















K31RD5040OP840DMW

KOMBIC 200 RD 5000 IP44 NW OPAL DA MA/WH

PHOTOMETRIC DATA:







	H (m)	D (m)	Emax	Emed
	1	1,61	2461	1247
	2	3,22	615	312
	3	4,84	273	139
1	4	6,45	154	78



ACCESORIES:

Optical



Product code: ADRD250W

Description:

KOMBIC ACC. Ø250 ADAPTER RING WH.



Product code: DITRRD240B

Description:

DOMO 220/KOMBIC ACC.TRANSP GLASS BK.



Product code:

Description:

DITRRD240G DOMO 220/KOMBIC ACC.TRANSP GLASS GR.

DITRRD240W DOMO 220/KOMBIC ACC.TRANSP GLASS WH.



Product code: RIRD240B

Description:

DOMO 220/KOMBIC ACC. DECO RING BK.



Product code:

Description:

RIRD240G DOMO 220/KOMBIC ACC. DECO RING GR. RIRD240W DOMO 220/KOMBIC ACC. DECO RING WH.



