KOMBIC 200 DOWNLIGHT




K31SQ4040OP830NRW



KOMBIC 200 SQ 4000 IP44 WW OPAL BR/WH

Description:

Square recessed downlight model KOMBIC 200 SQ, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and bright metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model for MID-POWER LED, with 3000K colour temperature and CRI 80 and control gear included. IP44 protection rating. Insulation class II. Photobiological safety group 0. Lifetime: 50.000h L80 B10



BRILLIANT METALLIC POLYCARBONATE Finish:

Weight: 822 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.024 lm °K: 3000 Plum: 25,4W CRI: 80 Efficacy: 79,7 lm/w 3 MacAdam:

Type: MID POWER TRIDONIC Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

24W Power:

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:






















KOMBIC 200 DOWNLIGHT




K31SQ4040OP830NRW

KOMBIC 200 SQ 4000 IP44 WW OPAL BR/WH

PHOTOMETRIC DATA:





alpha = 90,6°	H (m)	D (m)	Emax	Emed
	1	2,02	1077	464
	2	4,04	269	116
	3	6,06	120	52
	4	8,08	67	29

Product datasheet

KOMBIC 200 DOWNLIGHT



ACCESORIES:

Assembly



Product code: Description:

BORE404 DOMO SQ/KOMBIC SQ ACC. REC BOX

ACCESORIES:

Optical



Product code: Description: Product code: Description:

DITRSQ240B DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS BK. DITRSQ240W DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS WH.



Product code: Description: Product code: Description:

FRSQ235B DOMO SQ/KOMBIC SQ ACC. DECO FRAME BK. FRSQ235W DOMO SQ/KOMBIC SQ ACC. DECO FRAME WH.