KOMBIC 200 DOWNLIGHT

Worktitude for light

K31SQ5040OP840NRW




KOMBIC 200 SQ 5000 IP44 NW OPAL BR/WH

Description:

Square recessed downlight model KOMBIC 200 SQ, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and bright metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model for MID POWER LED, with 4000K colour temperature and CRI 80 and control gear included. IP44 protection rating. Insulation class II. Lifetime: 50.000h L70 B10

Finish: BRILLIANT METALLIC POLYCARBONATE

Weight: 1.536 g



Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 3.494 lm
 °K:
 4000

 Plum:
 38,1W
 CRI:
 80

 Efficacy:
 91,7 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L70 B10 (Ta=25°C) Gear: Electronic

Power: 36W

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU














KOMBIC 200 DOWNLIGHT





K31SQ5040OP840NRW

KOMBIC 200 SQ 5000 IP44 NW OPAL BR/WH

PHOTOMETRIC DATA:







H (m)	D (m)	Emax	Emed	
1	2,02	1835	791	
2	4,04	459	198	
3	6,06	204	88	
4	8,08	115	49	

Product datasheet

KOMBIC 200 DOWNLIGHT



ACCESORIES:

Assembly



Product code: Description:

BORE404 DOMO SQ/KOMBIC SQ ACC. REC BOX

ACCESORIES:

Optical



Product code: Description:

DITRSQ240B DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS BK. DITRSQ240W




Product code: Description:

ITRSQ240W DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS WH.



Product code: Description:

FRSQ235B DOMO SQ/KOMBIC SQ ACC. DECO FRAME BK.



Product code: Description:

FRSQ235W DOMO SQ/KOMBIC SQ ACC. DECO FRAME WH.

Data according to regulations 2019/2020/EU and 2019/2015/EU