

KOMBIC 200 DOWNLIGHT

K32RD4040OP840NMW




KOMBIC 200 G2 RD 4000 IP44 NW OP MA/W

Description:

Round recessed downlight KOMBIC 200 G2 RD 4000 Reflector made of recycled polycarbonate. Inner reflector finished in mat metallized. Elliptical optic option is the perfect choice for lighting walkways and longitudinal areas such as counters or areas adjacent to work areas. This product allows for increased spacing between luminaires, reducing the effect of residual light on walls and providing a pleasant atmosphere in the space. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 4000K and CRI80. Electronic ON OFF gear included. IP44 rated. Insulation Class II. Photobiological safety group 0. LED life time: 71.000 L80 B10. Available finish: White. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate

Weight: 749 g




Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	3.133 lm	°K :	4000
Plum:	24,10W	CRI :	80
Efficacy:	130 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	71.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	21,5W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:




KOMBIC 200 DOWNLIGHT

K32RD4040OP840NMW


KOMBIC 200 G2 RD 4000 IP44 NW OP MA/W

PHOTOMETRIC DATA :



ACCESORIES :

Optical




Product code:

ADRD250W

Description:

KOMBIC ACC. Ø250 ADAPTER RING WH.



Product code:

DITRRD240B

Description:

DOMO 220/KOMBIC ACC.TRANSP GLASS BK.



Product code:


DITRRD240G

Description:

DOMO 220/KOMBIC ACC.TRANSP GLASS GR.

DITRRD240W

DOMO 220/KOMBIC ACC.TRANSP GLASS WH.



Product code:

RIRD240B

Description:

DOMO 220/KOMBIC ACC. DECO RING BK.



Product code:

RIRD240G

Description:

DOMO 220/KOMBIC ACC. DECO RING GR.

RIRD240W

DOMO 220/KOMBIC ACC. DECO RING WH.