

## KOMBIC 200 DOWNLIGHT

K32SQ30400P830NRW




## KOMBIC 200 G2 SQ 3000 IP44 WW OP BR/W

## Description:


Round recessed downlight KOMBIC 200 G2 SQ 3000 Reflector made of recycled polycarbonate. Inner reflector finished in bright metallized. Elliptical optic option is the perfect choice for lighting walkways and longitudinal areas such as counters or areas adjacent to work areas. This product allows for increased spacing between luminaires, reducing the effect of residual light on walls and providing a pleasant atmosphere in the space. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP44 rated. Insulation Class II. Photobiological safety group 0. LED life time: 60.000 L80 B10. Available finish: White. Environmental Product Declaration - EPD® available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** BRILLIANT METALLIC POLYCARBONATE

**Weight:** 853 g

**Installation:** Recessed

## TECHNICAL SPECIFICATIONS:

<b>Light output:</b>	1.970 lm	<b>°K :</b>	3000
<b>Plum:</b>	16,7W	<b>CRI :</b>	80
<b>Efficacy:</b>	118 lm/w	<b>MacAdam:</b>	3
<b>Type:</b>	COB	<b>Power Supply:</b>	220-240V 50/60Hz
<b>LED Lifetime:</b>	82.000 L80 B10 (Ta=25°C)	<b>Gear:</b>	Electronic
<b>Power:</b>	14,5W		

*Light output tolerance +/- 10%*


## CUSTOM MADE OPTIONS:




KOMBIC 200 DOWNLIGHT

K32SQ30400P830NRW

KOMBIC 200 G2 SQ 3000 IP44 WW OP BR/W

PHOTOMETRIC DATA :



## ACCESORIES :

### Assembly



**Product code:**


BORE404

**Description:**

DOMO SQ/KOMBIC SQ ACC. REC BOX

## ACCESORIES :

### Optical



**Product code:**

DITRSQ240B

**Description:**

DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS BK.




**Product code:**

DITRSQ240W

**Description:**

DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS WH.



**Product code:**

FRSQ235B

**Description:**

DOMO SQ/KOMBIC SQ ACC. DECO FRAME BK.



**Product code:**

FRSQ235W

**Description:**

DOMO SQ/KOMBIC SQ ACC. DECO FRAME WH.