KOMBIC 200 DOWNLIGHT

K32SQ4040OP840NRW




KOMBIC 200 G2 SQ 4000 IP44 NW OP BR/W

Description:

Round recessed downlight KOMBIC 200 G2 SQ 4000 Reflector made of recycled polycarbonate. Inner reflector finished in bright metallized. Elliptical optic option is the perfect choice for lighting walkways and longitudinal areas such as counters or areas adjacent to work areas. This product allows for increased spacing between luminaires, reducing the effect of residual light on walls and providing a pleasant atmosphere in the space. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 4000K and CRI80. Electronic ON OFF gear included. IP44 rated. Insulation Class II. Photobiological safety group 0. LED life time: 60.000 L80 B10. Available finish: White Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

BRILLIANT METALLIC POLYCARBONATE Finish:

Weight: 857 g



Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.886 lm °K: 4000 Plum: 24,1W CRI: 80

Efficacy: 119,8 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 71.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 21,5W

Light output tolerance +/- 10%

















CUSTOM MADE OPTIONS:





















KOMBIC 200 DOWNLIGHT



K32SQ4040OP840NRW


KOMBIC 200 G2 SQ 4000 IP44 NW OP BR/W


PHOTOMETRIC DATA:


K32SQ4040OP840NRW η = 101%

lmax = 524 cd/klmUTE: 1,01C

CIE: 63 96 100 100 101







Product datasheet

KOMBIC 200 DOWNLIGHT



ACCESORIES:

Assembly



Product code: Description:

BORE404 DOMO SQ/KOMBIC SQ ACC. REC BOX

ACCESORIES:

Optical



Product code: Product code

DITRSQ240B DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS BK. DITRSQ240W




Product code: Description:

TRSQ240W DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS WH.



Product code: Description:

FRSQ235B DOMO SQ/KOMBIC SQ ACC. DECO FRAME BK.



Product code: Description:

FRSQ235W DOMO SQ/KOMBIC SQ ACC. DECO FRAME WH.