

KOMBIC 200 DOWNLIGHT


K32SQ70400P830DRW




KOMBIC 200 G2 SQ 7000 IP44 WW OP DA BR/W

Description:

Round recessed downlight KOMBIC 200 G2 SQ 7000 Reflector made of recycled polycarbonate. Inner reflector finished in bright metallized. Elliptical optic option is the perfect choice for lighting walkways and longitudinal areas such as counters or areas adjacent to work areas. This product allows for increased spacing between luminaires, reducing the effect of residual light on walls and providing a pleasant atmosphere in the space. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 3000K and CRI80. Electronic DALI gear included. IP44 rated. Insulation Class II. Photobiological safety group 0. LED life time: 60.000 L80 B10. Available finish: White. Environmental Product Declaration - EPD® available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: BRILLIANT METALLIC POLYCARBONATE**Weight:** 1.770 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	4.950 lm	°K :	3000
Plum:	51W	CRI :	80
Efficacy:	97,1 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	66.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI2
Power:	45,2W		


Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 200 DOWNLIGHT

K32SQ70400P830DRW

KOMBIC 200 G2 SQ 7000 IP44 WW OP DA BR/W

PHOTOMETRIC DATA :



ACCESORIES :

Assembly



Product code:

BORE404

Description:

DOMO SQ/KOMBIC SQ ACC. REC BOX

ACCESORIES :

Optical



Product code:

DITRSQ240B

Description:

DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS BK.



Product code:

DITRSQ240W

Description:

DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS WH.



Product code:

FRSQ235B

Description:

DOMO SQ/KOMBIC SQ ACC. DECO FRAME BK.



Product code:

FRSQ235W

Description:

DOMO SQ/KOMBIC SQ ACC. DECO FRAME WH.