



KOMBIC 70 DOWNLIGHT

K711523EL827N66



KOMBIC 70 1500 IP23 827 EL SER

Description:

Recessed round downlight model KOMBIC 70. R-PC FR WHITE tm recycled polycarbonate reflector with bromine-free flame retardant. Flammability degree V0 according to UL94. Elliptical optics, which increase the distance between luminaires and reduce the effect of residual light on the walls. Ideal for lighting passageways, longitudinal areas such as countertops or areas adjacent to work areas Aluminum injection heat sink, with a black finish. COB LED, with 2700K color temperature with CRI80. Electronic equipment ON OFF included. With an IP43 degree of protection. Insulation class II. Photobiological safety group 0. Hours of life: 66,000 L90 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Luminous flux tolerance $\pm 4\%$ depending on the finish.


Finish: SERENA Palette

Weight: 190 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	938 lm	°K :	2700
Plum:	10W	CRI :	80
Efficacy:	93,8 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	COB	Gear:	Electronic
LED Lifetime:	66.000 L90 B10 (Ta=25°C)		
Power:	8,4W		

Light output tolerance $\pm 10\%$ 

CUSTOM MADE OPTIONS:

