

KOMBIC 70 DOWNLIGHT


K711523EL927NWW



KOMBIC 70 1500 IP23 9VWW ELI. WH/WH

Description:


KOMBIC 70 round recessed downlight by LAMP. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white. Elliptical optic option is the perfect choice for lighting walkways and longitudinal areas such as counters or areas adjacent to work areas. This product allows for increased spacing between luminaires, reducing the effect of residual light on walls and providing a pleasant atmosphere in the space. Heatsink made of die-cast aluminium with black finish. LED COB, colour temperature 2700K with IRC90. Luminaire with electronic wiring included. Insulation class II. LED life time: 66000 L90 B10. With IP23 degree of protection. Group 0 photobiological safety.



Finish: Matte white RAL 9010

Weight: 190 g


Installation: Recessed



TECHNICAL SPECIFICATIONS:

Light output:	723 lm	°K :	2700
Plum:	9,5W	CRI :	90
Efficacy:	76,1 lm/w	R9 :	59
Type:	COB	MacAdam:	3
LED Lifetime:	66.000 L90 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	8,4W	Gear:	Electronic

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 70 DOWNLIGHT

K711523EL927NWW

KOMBIC 70 1500 IP23 9VWW ELI. WH/WH

PHOTOMETRIC DATA :

K711523EL927NWW
 $\eta = 100\%$
 $I_{max} = 2048 \text{ cd/klm}$
 UTE: 1,00A
 CIE: 90 97 100 100 100

