



## KOMBIC 70 DOWNLIGHT

K711523RF830DWW




## KOMBIC 70 1500 IP23 WW RF FL DA WH/WH

**Description:**

KOMBIC 70 round recessed downlight by LAMP. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring Dali included. Insulation class II. LED life time: 66000 L90 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector Flood to achieve a controlled light distribution and low glare level, less than UGR<19

**Finish:** Matte white RAL 9010**Weight:** 190 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.174 lm	<b>°K :</b>	3000
<b>Plum:</b>	9,5W	<b>CRI :</b>	80
<b>Efficacy:</b>	123,6 lm/w	<b>MacAdam:</b>	3
<b>UGR:</b>	<19	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Type:</b>	COB	<b>Gear:</b>	Adjustable DALI
<b>LED Lifetime:</b>	66.000 L90 B10 (Ta=25°C)		
<b>Power:</b>	8,4W		

**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**

KOMBIC 70 DOWNLIGHT

K711523RF830DWW

KOMBIC 70 1500 IP23 WW RF FL DA WH/WH

PHOTOMETRIC DATA :

