



KOMBIC 70 DOWNLIGHT

K711523RW940NWW



KOMBIC 70 1500 IP23 9NW RF WFL WH/WH

Description:

KOMBIC 70 round recessed downlight by LAMP. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring included. Insulation class II. LED life time: 66000 L90 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector Wide Flood to achieve a controlled light distribution and low glare level.

Finish: Matte white RAL 9010**Weight:** 190 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

| | | | |
|----------------------|--------------------------|----------------------|------------------|
| Light output: | 1.002 lm | °K : | 4000 |
| Plum: | 9,5W | CRI : | 90 |
| Efficacy: | 105,5 lm/w | R9 : | 68 |
| Type: | COB | MacAdam: | 3 |
| LED Lifetime: | 66.000 L90 B10 (Ta=25°C) | Power Supply: | 220-240V 50/60Hz |
| Power: | 8,4W | Gear: | Electronic |

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 70 DOWNLIGHT

K711523RW940NWW

KOMBIC 70 1500 IP23 9NW RF WFL WH/WH

PHOTOMETRIC DATA :

