

KOMBIC 70 DOWNLIGHT


K711523WF830NWW



KOMBIC 70 1500 IP23 WW WFL WH/WH


Description:

KOMBIC 70 round recessed downlight by LAMP. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring included. Insulation class II. LED life time: 66000 L90 B10. With IP23 degree of protection. Group 0 photobiological safety. Optic Wide Flood to achieve a controlled light distribution and low glare level, less than UGR<19



Finish: Matte white RAL 9010

Weight: 190 g




Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	973 lm	°K :	3000
Plum:	9,5W	CRI :	80
Efficacy:	102,5 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	COB	Gear:	Electronic
LED Lifetime:	66.000 L90 B10 (Ta=25°C)		
Power:	8,4W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 70 DOWNLIGHT

K711523WF830NWW

KOMBIC 70 1500 IP23 WW WFL WH/WH

PHOTOMETRIC DATA :

