



KOMBIC 70 DOWNLIGHT

K711523WF927NWW



KOMBIC 70 1500 IP43 9VWW WFL WH/WH

Description:

KOMBIC 70 round recessed downlight by LAMP. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring included. Insulation class II. LED life time: 66000 L90 B10. With IP43 degree of protection. Group 0 photobiological safety. Optic Wide Flood to achieve a controlled light distribution and low glare level, less than UGR<19


Finish: Matte white RAL 9010

Weight: 190 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	795 lm	°K :	2700
Plum:	9,5W	CRI :	90
Efficacy:	83,6 lm/w	R9 :	59
UGR:	<19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	66.000 L90 B10 (Ta=25°C)	Gear:	Electronic
Power:	8,4W		

Light output tolerance +/- 10%


CUSTOM MADE OPTIONS:



KOMBIC 70 DOWNLIGHT

K711523WF927NWW

KOMBIC 70 1500 IP43 9VWW WFL WH/WH

PHOTOMETRIC DATA :

