


KOMBIC 70 DOWNLIGHT

K711523WW930NBB

**KOMBIC 70 1500 IP43 9WW WW BK/BK****Description:**

LAMP Round recessed downlight KOMBIC 70 1500 Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Wallwasher optic option, suitable for vertical plane lighting or work areas surroundings. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 3000K and CRI90. Electronic ON OFF gear included. IP43 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. Available finishes: White and black.

Finish: Matte black RAL 9011**Weight:** 210 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	543 lm	°K :	3000
Plum:	10W	CRI :	90
Efficacy:	54,3 lm/w	R9 :	68
Type:	COB	MacAdam:	3
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	8,4W	Gear:	Electronic

Light output tolerance +/- 10%

KOMBIC 70 DOWNLIGHT

K711523WW930NBB

KOMBIC 70 1500 IP43 9WW WW BK/BK

PHOTOMETRIC DATA :

