### **KOMBIC 70 DOWNLIGHT**

### K711544OP927D66



### KOMBIC 70 1500 IP44 927 OPAL DA SER

### Description:

Recessed round downlight model KOMBIC 70. R-PC FR WHITE tm recycled polycarbonate reflector with brominefree flame retardant. Flammability degree V0 according to UL94. Opal optical film. Aluminum injection heatsink, with a black finish. COB LED, with 2700K color temperature with CRI90. DALI electronic equipment included. With an IP44 degree of protection. Insulation class II. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Luminous flux tolerance±7% depending on the finish.





Finish: SERENA Palette

Weight: 190 g

Installation: Recessed

### **TECHNICAL SPECIFICATIONS:**

Light output: 642 lm °K: 2700 Plum: 10W CRI: 90 Efficacy: 64,2 lm/w R9: 61 Type: СОВ MacAdam: 3

LED Lifetime: 66.000 L90 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz 8,4W Gear: Power: Adjustable DALI

# Light output tolerance +/- 10%

























## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU









