



KOMBIC 70 DOWNLIGHT

K711544OP940N66




KOMBIC 70 1500 IP44 940 OPAL SER

Description:

Recessed round downlight model KOMBIC 70. R-PC FR WHITE tm recycled polycarbonate reflector with bromine-free flame retardant. Flammability degree V0 according to UL94. Opal optical film. Aluminum injection heatsink, with a black finish. COB LED, with 4000K color temperature with CRI90. Electronic equipment ON OFF included. With an IP44 degree of protection. Insulation class II. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Luminous flux tolerance $\pm 7\%$ depending on the finish.

Finish: SERENA Palette**Weight:** 190 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	697 lm	°K :	4000
Plum:	10W	CRI :	90
Efficacy:	69,7 lm/w	R9 :	61
Type:	COB	MacAdam:	3
LED Lifetime:	66.000 L90 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	8,4W	Gear:	Electronic

Light output tolerance $\pm 10\%$ **CUSTOM MADE OPTIONS:**