


KOMBIC 70 DOWNLIGHT

K711565OP840DWW




KOMBIC 70 1500 IP65 NW OPAL DA WH/WH

Description:

KOMBIC 70 round recessed downlight by LAMP. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and opal optical sheet. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insulation class II. LED life time: 66000 L90 B10. With IP65 degree of protection. Group 0 photobiological safety.

Finish: Matte white RAL 9010**Weight:** 190 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	981 lm	°K :	4000
Plum:	9,5W	CRI :	80
Efficacy:	103,3 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	66.000 L90 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	8,4W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 70 DOWNLIGHT

K711565OP840DWW

KOMBIC 70 1500 IP65 NW OPAL DA WH/WH

PHOTOMETRIC DATA :

